



44506-5250 ER6022-031ME

Safety rope pull E-stop switch, up to 80m, E-stop, contact 3 NC + NO, wiring 3 x M20

Технические характеристики

Number of contacts, normally-open	1
Number of contacts, normally-closed	3
Max. length of pull cord	80 m
Number of actuation directions	1
Mounting position	Left or Right
Material housing	Diecast aluminium
Color	Yellow
E-stop button	Included
With LED indicator	✘
With tension indication	✔
Number of conduits	3
Conduit size	M20
Ambient temperature	-25-80 °C
Degree of protection (IP)	IP67
Degree of protection (NEMA)	6

Дополнительные принадлежности



44506-2705 RK5

Safety rope pull E-stop switch accessory, rope kit 5m



44506-2710 RK10

Safety rope pull E-stop switch accessory, rope kit 10m



44506-2720 RK20

Safety rope pull E-stop switch accessory, rope kit 20m



44506-2750 RK50

Safety rope pull E-stop switch accessory, rope kit 50m

Загрузка

Библиотека дву-
/трехмерных CAD
рисунков



**ER6022 Rope Pull
Emergency Stop Switch**
Спецификация

EN PDF 389,3 КБ



Machine Safety
Каталог

RU PDF 11,9 МБ



**Safety Component
Selection Guide**
Брошюра

EN PDF 10,8 МБ



**Safety Solution
Advanced Guide**
Руководство

EN PDF 2,6 МБ



**Safety Solution Basic
Guide**
Руководство

EN PDF 14,4 МБ

УСЛОВИЯ ПОЛЬЗОВАНИЯ ВЕБ-САЙТОМ

Этот PDF-документ был создан на основании веб-сайта Европейского подразделения промышленной автоматизации компании OMRON 28 June, 2022. Нажмите здесь, чтобы ознакомиться с [уведомление о правах](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU