



CJ1W-ID231

Модуль расширения для CJ1, 32 входа, 24VDC, Fujitsu-разъем (поставляется отдельно)

Технические характеристики

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	32
Digital input type	PNP/NPN
Permitted voltage at input	20.4-26.4 V
OFF/ON delay	0-32 ms
Number of digital outputs	0
Digital output type	None
Output current	0 A
Short-circuit protected outputs	✘
I/O connection type	FCN (plug not included)
Number of I/O connectors	1
Detachable I/O connector	✔
Suitable for safety functions	✘
Number of IOV (V+) terminals	0
Number of IOG (V-) terminals	0
Number of COM terminals	4
Height	90 mm
Width	20 mm
Depth	66.5 mm
Weight	64 g

Дополнительные принадлежности



G70V-SID16P

Relay terminal, PLC Input, 16 channels, NPN, Push-in terminals



G70V-SID16P-1

Relay terminal, PLC Input, 16 channels, PNP, Push-in terminals

P2RV-4-100IFC

G2RV interface cable for use between CJ1W-ID231/ID233/ID261 and 4 P2RV-8-I-F modules, 1 m

P2RV-4-200IFC

G2RV interface cable for use between CJ1W-ID231/ID233/ID261 and 4 P2RV-8-I-F modules, 2 m



P2RVC-8-I-5

Interface unit for G2RV-SR/G3RV-SR Push-in, PLC Input, 8 channels, NPN, 30V AC/DC, Total 2A, Push-in



P2RVC-8-I-5-1

Interface unit for G2RV-SR/G3RV-SR Push-in, PLC Input, 8 channels, PNP, 30V AC/DC, Total 2A, Push-in



P2RVC-8-I-7-1

Interface unit for G2RV-SR/G3RV-SR Screw, PLC Input, 8 channels, PNP, 30V AC/DC, Total 2A, Rising-up screw




XW2D-40G6

General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points



XW2K-40G-O32A

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



XW2K-40G-O32A-IN

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input, Signal: 0.5 A, Power: 7 A, NPN, 30 VDC, DIN rail horizontal and vertical mounting



XW2Z-0100BF-L

I/O connection cable, unshielded, FCN40 to MIL40, 1 m



XW2Z-0100BN-L

I/O connection cable, unshielded, FCN40 to open ends, 1 m



XW2Z-0200BF-L

I/O connection cable, unshielded, FCN40 to MIL40, 2 m



XW2Z-0200BN-L

I/O connection cable, unshielded, FCN40 to open ends, 2 m



XW2Z-0300BN-L

I/O connection cable, unshielded, FCN40 to open ends, 3 m



XW2Z-050B

I/O connection cable, FCN40 to MIL40, 0.5 m



XW2Z-100B

I/O connection cable, FCN40 to MIL40, 1 m



XW2Z-150B

I/O connection cable, FCN40 to MIL40, 1.5 m



XW2Z-200B

I/O connection cable, FCN40 to MIL40, 2 m



XW2Z-300B

I/O connection cable, FCN40 to MIL40, 3 m



XW2Z-RI100C-75

I/O connection cable, with shield connection, FCN40 to 2 x MIL20, 1 m / 0.75 m



XW2Z-RI200C-175

I/O connection cable, with shield connection, FCN40 to 2 x MIL20, 2 m / 1.75 m

Библиотека дву-
/трехмерных CAD
рисунков



CJ1W-ID/IA Спецификация

EN PDF 3,1 МБ



CJ2 CPU Units Hardware Руководство пользователя

RU PDF 19,6 МБ



CJ2-Series Спецификация

EN PDF 14,3 МБ