



## CJ1W-MD232

Модуль расширения для CJ1, 16 входов и 16 выходов (PNP), MIL-разъем (поставляется отдельно)

# Технические характеристики

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	16
Digital input type	PNP/NPN
Permitted voltage at input	20.4-26.4 V
OFF/ON delay	0-32 ms
Number of digital outputs	16
Digital output type	PNP
Permitted voltage at output	10.2-26.4 V
Output current	0.5 A
Short-circuit protected outputs	✘
I/O connection type	MIL (plug not included)
Number of I/O connectors	2
Detachable I/O connector	✔
Suitable for safety functions	✘
Number of IOV (V+) terminals	2
Number of IOG (V-) terminals	2
Number of COM terminals	2
Height	90 mm
Width	31 mm
Depth	83.6 mm
Weight	100 g

# Дополнительные принадлежности



**G70A-ZOC16-4 DC24**

Output Terminal Block for Relay or SSR, 16-point, for PNP output units



**G70V-SID16P**

Relay terminal, PLC Input, 16 channels, NPN, Push-in terminals



**G70V-SID16P-1**

Relay terminal, PLC Input, 16 channels, PNP, Push-in terminals



**G70V-SOC16P-1**

Relay terminal, PLC Output, 16 channels, PNP, Push-in terminals



**XW2D-20G6**

General-purpose I/O terminal block, MIL20 socket, M3 captive screws, 20 points



**XW2K-20G-T**

General purpose interface wiring system with push-in plus technology, 20 points MIL connector, Input/Output, 1 A, NPN/PNP, 125 VAC, 30 VDC, DIN rail horizontal and vertical mounting



**XW2Z-0100DD-L**

I/O connection cable, unshielded, MIL20 to MIL20, 1 m




**XW2Z-0100DL-L**

I/O connection cable, unshielded, MIL20 to open ends, 1 m



**XW2Z-0200DD-L**

I/O connection cable, unshielded, MIL20 to MIL20, 2 m



**XW2Z-0200DL-L**

I/O connection cable, unshielded, MIL20 to open ends, 2 m



**XW2Z-0500DL-L**

I/O connection cable, unshielded, MIL20 to open ends, 5 m

**XW2Z-100X**

I/O connection cable, MIL20 to MIL20, 1 m

XW2Z-200X

I/O connection cable, MIL20 to MIL20, 2 m



XW2Z-RI50C

I/O connection cable, with shield connection, FCN24 to MIL20 for G70A-ZOC16-3 / G70A-ZIM16-5, 5 m



XW2Z-RO50C

I/O connection cable, MIL20 to MIL20 for XW2\*-20G\* or G70A-ZOC16-3, 0.5 m

## Загрузка

Библиотека дву-  
/трехмерных CAD  
рисунков



**CJ1W-MD**  
Спецификация

EN PDF 3,4 МБ



**CJ2 CPU Units Hardware**  
Руководство  
пользователя

RU PDF 19,6 МБ



**CJ2-Series**  
Спецификация

EN PDF 14,3 МБ

### УСЛОВИЯ ПОЛЬЗОВАНИЯ ВЕБ-САЙТОМ

Этот PDF-документ был создан на основании веб-сайта Европейского подразделения промышленной автоматизации компании OMRON 8 August, 2022. Нажмите здесь, чтобы ознакомиться с [уведомление о правах](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU