



CJ1W-MD233

Модуль расширения для CJ1, 16 входов и 16 выходов (NPN), 2 x MIL-разъем (поставляется отдельно)

Технические характеристики

| | |
|---------------------------------|-------------------------|
| I/O system | CJ I/O Bus |
| Expansion unit type | Basic I/O Unit |
| Type of module | Digital I/O |
| Number of digital inputs | 16 |
| Digital input type | PNP/NPN |
| Permitted voltage at input | 20.4-26.4 V |
| OFF/ON delay | 0-32 ms |
| Number of digital outputs | 16 |
| Digital output type | NPN |
| Permitted voltage at output | 10.2-26.4 V |
| Output current | 0.5 A |
| Short-circuit protected outputs | ✘ |
| I/O connection type | MIL (plug not included) |
| Number of I/O connectors | 2 |
| Detachable I/O connector | ✔ |
| Suitable for safety functions | ✘ |
| Number of IOV (V+) terminals | 2 |
| Number of IOG (V-) terminals | 2 |
| Number of COM terminals | 2 |
| Height | 90 mm |
| Width | 31 mm |
| Depth | 83.6 mm |
| Weight | 90 g |

Дополнительные принадлежности



G70A-ZOC16-3 DC24

Output Terminal Block for Relay or SSR, 16-point, for NPN output units



G70V-SID16P

Relay terminal, PLC Input, 16 channels, NPN, Push-in terminals



G70V-SID16P-1

Relay terminal, PLC Input, 16 channels, PNP, Push-in terminals



XW2D-20G6

General-purpose I/O terminal block, MIL20 socket, M3 captive screws, 20 points




XW2K-20G-T

General purpose interface wiring system with push-in plus technology, 20 points MIL connector, Input/Output, 1 A, NPN/PNP, 125 VAC, 30 VDC, DIN rail horizontal and vertical mounting



XW2Z-0100DD-L

I/O connection cable, unshielded, MIL20 to MIL20, 1 m




XW2Z-0100DL-L

I/O connection cable, unshielded, MIL20 to open ends, 1 m



XW2Z-0200DD-L

I/O connection cable, unshielded, MIL20 to MIL20, 2 m



XW2Z-0200DL-L

I/O connection cable, unshielded, MIL20 to open ends, 2 m



XW2Z-0500DL-L

I/O connection cable, unshielded, MIL20 to open ends, 5 m

XW2Z-100X

I/O connection cable, MIL20 to MIL20, 1 m

XW2Z-200X

I/O connection cable, MIL20 to MIL20, 2 m



XW2Z-RO50C

I/O connection cable, MIL20 to MIL20 for XW2*-20G* or G70A-ZOC16-3, 0.5 m

Загрузка

Библиотека дву-
/трехмерных CAD
рисунков



CJ1W-MD Спецификация

EN PDF 3,4 МБ



CJ2 CPU Units Hardware Руководство пользователя

RU PDF 19,6 МБ



CJ2-Series Спецификация

EN PDF 14,3 МБ

УСЛОВИЯ ПОЛЬЗОВАНИЯ ВЕБ-САЙТОМ

Этот PDF-документ был создан на основании веб-сайта Европейского подразделения промышленной автоматизации компании OMRON 8 August, 2022. Нажмите здесь, чтобы ознакомиться с [уведомление о правах](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU