



## CJ1W-MD261

Модуль расширения для CJ1, 32 входа и 32 выхода (NPN), 2 x Fujitsu-разъем (поставляется отдельно)

# Технические характеристики

I/O system	CJ I/O Bus
Expansion unit type	Basic I/O Unit
Type of module	Digital I/O
Number of digital inputs	32
Digital input type	PNP/NPN
Permitted voltage at input	20.4-26.4 V
OFF/ON delay	0-32 ms
Number of digital outputs	32
Digital output type	NPN
Permitted voltage at output	10.2-26.4 V
Output current	0.3 A
Short-circuit protected outputs	✘
I/O connection type	FCN (plug not included)
Number of I/O connectors	2
Detachable I/O connector	✔
Suitable for safety functions	✘
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Number of COM terminals	4
Height	90 mm
Width	31 mm
Depth	66.5 mm
Weight	110 g

# Дополнительные принадлежности



**G70A-ZOC16-3 DC24**

Output Terminal Block for Relay or SSR, 16-point, for NPN output units



**G70V-SID16P**

Relay terminal, PLC Input, 16 channels, NPN, Push-in terminals



**G70V-SID16P-1**

Relay terminal, PLC Input, 16 channels, PNP, Push-in terminals

**P2RV-4-100IFC**

G2RV interface cable for use between CJ1W-ID231/ID233/ID261 and 4 P2RV-8-I-F modules, 1 m

**P2RV-4-200IFC**

G2RV interface cable for use between CJ1W-ID231/ID233/ID261 and 4 P2RV-8-I-F modules, 2 m



**P2RVC-8-I-5**

Interface unit for G2RV-SR/G3RV-SR Push-in, PLC Input, 8 channels, NPN, 30V AC/DC, Total 2A, Push-in



**P2RVC-8-I-5-1**

Interface unit for G2RV-SR/G3RV-SR Push-in, PLC Input, 8 channels, PNP, 30V AC/DC, Total 2A, Push-in



**P2RVC-8-I-7-1**

Interface unit for G2RV-SR/G3RV-SR Screw, PLC Input, 8 channels, PNP, 30V AC/DC, Total 2A, Rising-up screw



**XW2D-40G6**

General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points




**XW2K-40G-O32A**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



**XW2K-40G-O32A-IN**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input, Signal: 0.5 A, Power: 7 A, NPN, 30 VDC, DIN rail horizontal and vertical mounting



**XW2K-40G-O32B**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting



**XW2K-40G-O32B-OUT**

PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Output, Signal: 0.5 A, Power: 7 A, NPN, 30 VDC, DIN rail horizontal and vertical mounting



**XW2Z-0100BF-L**

I/O connection cable, unshielded, FCN40 to MIL40, 1 m



**XW2Z-0100BH-L02**

I/O connection cable, unshielded, FCN40 to 2 x MIL20, 1 m, cross-wired



**XW2Z-0100BN-L**

I/O connection cable, unshielded, FCN40 to open ends, 1 m



**XW2Z-0200BF-L**

I/O connection cable, unshielded, FCN40 to MIL40, 2 m



**XW2Z-0200BH-L02**

I/O connection cable, unshielded, FCN40 to 2 x MIL20, 2 m, cross-wired



**XW2Z-0200BN-L**

I/O connection cable, unshielded, FCN40 to open ends, 2 m



**XW2Z-0300BN-L**

I/O connection cable, unshielded, FCN40 to open ends, 3 m



**XW2Z-050B**

I/O connection cable, FCN40 to MIL40, 0.5 m



**XW2Z-100B**

I/O connection cable, FCN40 to MIL40, 1 m



**XW2Z-150B**

I/O connection cable, FCN40 to MIL40, 1.5 m



**XW2Z-200B**

I/O connection cable, FCN40 to MIL40, 2 m



**XW2Z-300B**

I/O connection cable, FCN40 to MIL40, 3 m



**XW2Z-RI100C-75**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20, 1 m / 0.75 m



**XW2Z-RI200C-175**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20, 2 m / 1.75 m



**XW2Z-RO100C-75**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 1 m / 0.75 m



**XW2Z-RO200C-150**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 2 m / 1.5 m



**XW2Z-RO200C-175**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70 A-ZOC16-3, 2 m / 1.75 m



**XW2Z-RO300C-275**

I/O connection cable, with shield connection, FCN40 to 2 x MIL20 for G70A-ZOC16-3, 3 m / 2.75 m

## Загрузка

Библиотека дву-  
/трехмерных CAD  
рисунков



**CJ1W-MD**  
Спецификация

**EN** PDF 3,4 МБ



**CJ2 CPU Units Hardware**  
Руководство  
пользователя

**RU** PDF 19,6 МБ



**CJ2-Series**  
Спецификация

**EN** PDF 14,3 МБ

### УСЛОВИЯ ПОЛЬЗОВАНИЯ ВЕБ-САЙТОМ

Этот PDF-документ был создан на основании веб-сайта Европейского подразделения промышленной автоматизации компании OMRON 9 August, 2022. Нажмите здесь, чтобы ознакомиться с [уведомление о правах](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU