



D40Z-1C5

Дверной выключатель безопасн. бесконтактный, 1НО, кабель 5м, (требуется G9SX-NS или G9SP для достижения Категории 4/Plе)

Технические характеристики

Switch without actuator	×
Min. operating distance OFF to ON	5 mm
Max. operating distance ON to OFF	15 mm
Max. differential travel	20 %
Ambient temperature (operating)	-10-65 °C
Vibration resistance	10 to 55 to 10 Hz (single amplitude: 0.75 mm, double amplitude: 1.5 mm)
Min. shock resistance	300 m/s ²
Degree of protection (IP)	IP67
Material housing	PBT
Mounting method	M4 screws
Max. power consumption	0.5 W
Auxiliary monitoring output	Photocoupler output: 24 V DC, load current: 10 mA
LED indicators	Actuator detected (yellow), Actuator not detected (red)
Cable length	5 m
Number of connectable switches	30 max. (wiring length: 100 m max.)

Библиотека дву-
/трехмерных CAD
рисунков



D40Z Спецификация

EN PDF 2,4 МБ



Machine Safety Каталог

RU PDF 11,9 МБ



Safety Component Selection Guide Брошюра

EN PDF 10,8 МБ



Safety Interlock Switches Брошюра

EN PDF 1,5 МБ



Safety Solution Advanced Guide Руководство

EN PDF 2,6 МБ



Safety Solution Basic Guide Руководство

EN PDF 14,4 МБ