



## F3S-TGR-NLMX-21-05

Бесконтактный дверной выключ. безопас. F3S-TGR-N\_X, удлинённый, нерж. сталь, 2НЗ+1НО, кабель 5м

# Технические характеристики

Door switch type	Non-contact, Reed
Shape	Rectangular
Guard-lock	×
Coding	Uncoded
Material housing	Stainless steel
Ambient temperature (operating)	-20-80 °C
Door contacts NC	2
Door contacts NO	1
With LED indicator	×
Connection method	Cable
Cable length	5 m
Cable exit direction	Left
Degree of protection (IP)	IP67
Output type	Reed contact
Overall length	88 mm
Height of sensor	14 mm
Width sensor	25 mm
Switch without actuator	×

Библиотека дву-  
/трехмерных CAD  
рисунков



## F3S-TGR-N\_X Explosion proof Non-contact Safety Switches

Спецификация

EN PDF 401,9 КБ



## Machine Safety Каталог

RU PDF 11,9 МБ



## Safety Component Selection Guide

Брошюра

EN PDF 10,8 МБ



## Safety Interlock Switches

Брошюра

EN PDF 1,5 МБ



## Safety Solution Advanced Guide

Руководство

EN PDF 2,6 МБ



## Safety Solution Basic Guide

Руководство

EN PDF 14,4 МБ