



F3S-TGR-NM-PR-20-05

Бесконтактный дверной выключ. безопасн. F3S-TGR-N_R, миниатюрный, пластик, герконовый, 2НЗ, кабель 5м

Технические характеристики

Door switch type	Non-contact, Reed
Guard-lock	×
Coding	Uncoded
Material housing	Polyester
Ambient temperature (operating)	-25-80 °C
Door contacts NC	2
Door contacts NO	1
With LED indicator	×
Connection method	Cable
Cable length	5 m
Cable exit direction	Left
Degree of protection (IP)	IP69K
Output type	Reed contact
Shape	Rectangular miniature
Overall length	41 mm
Height of sensor	13 mm
Width sensor	26 mm
Switch without actuator	×

Библиотека дву-
/трехмерных CAD
рисунков



F3S-TGR-N_R Magnetic non-contact safety switches

Спецификация

EN PDF 1,3 МБ



Machine Safety Каталог

RU PDF 11,9 МБ



Safety Component Selection Guide

Брошюра

EN PDF 10,8 МБ



Safety Interlock Switches

Брошюра

EN PDF 1,5 МБ



Safety Solution Advanced Guide

Руководство

EN PDF 2,6 МБ



Safety Solution Basic Guide

Руководство

EN PDF 14,4 МБ