



F3S-TGR-NSMR-20-10

Бесконтактный дверной выключ. безопасн. F3S-TGR-N_R, маленький, нерж. сталь, герконовый, 2НЗ, кабель 10м

Технические характеристики

| | |
|---------------------------------|-------------------|
| Door switch type | Non-contact, Reed |
| Guard-lock | × |
| Coding | Uncoded |
| Material housing | Stainless steel |
| Ambient temperature (operating) | -25-105 °C |
| Door contacts NC | 2 |
| Door contacts NO | 1 |
| With LED indicator | × |
| Connection method | Cable |
| Cable length | 10 m |
| Cable exit direction | Left |
| Degree of protection (IP) | IP69K |
| Output type | Reed contact |
| Shape | Rectangular small |
| Overall length | 50 mm |
| Height of sensor | 13 mm |
| Width sensor | 25.5 mm |
| Switch without actuator | × |

Библиотека дву-
/трехмерных CAD
рисунков



F3S-TGR-N_R Magnetic non-contact safety switches

Спецификация

EN PDF 1,3 МБ



Machine Safety Каталог

RU PDF 11,9 МБ



Safety Component Selection Guide

Брошюра

EN PDF 10,8 МБ



Safety Interlock Switches

Брошюра

EN PDF 1,5 МБ



Safety Solution Advanced Guide

Руководство

EN PDF 2,6 МБ



Safety Solution Basic Guide

Руководство

EN PDF 14,4 МБ