



G2RV-SR500 12VDC

Реле 6 мм серии G2RV, черное, клеммы Push-in Plus, напряжение питания 12 V DC, ток 6 A

Технические характеристики

Transparent case	✓
With mechanical indicator	✓
Mounting method	DIN rail
Usage	Interface
Poles	1
Rated carry current	6 A
Coil voltage	12 V
Operation voltage	DC
Contact material	Ag alloy
Contact description	SPDT
Features	Diode, LED
Terminal	Push-in Plus



G2RV-1-S-AP-G 21VDC

Slimline input relay (6 mm width), SPDT, 50 mA, for replacement in G2RV-SR***-AP 24DC or 24 VAC/DC



G2RV-1-S-G 21VDC

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 24DC or 24 VAC/DC



G2RV-1-S-G DC11

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 12VDC



G2RV-1-S-G DC48

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 48VAC/DC, 100 VAC, 110 VAC, 200 VAC, 230 VAC



G2RV-1-SI-G 21VDC

Slimline relay (6 mm width), lockable test switch, SPDT, 6 A, for replacement in G2RV-SR701/501 24VDC or 24 VAC/DC

Библиотека дву-
/трехмерных CAD
рисунков



G2RV-SR/G3RV-SR Slim I/O Relay Спецификация

EN PDF 10,0 МБ



Industrial Relays Брошюра

RU PDF 2,8 МБ



Panel Building Брошюра

RU PDF 3,1 МБ



Relay Series Брошюра

RU PDF 2,0 МБ