



NXR-ILM08C-EIT





Удаленный терминал EtherNet/IP. Ведущее устройство IO-Link, 8 каналов, IP67.



Технические характеристики

Type of module	IO-Link master
Communication port(s)	EtherNet/IP, IO-Link
Number of digital inputs	8
Digital input type	IO-Link, PNP
Number of digital outputs	8
Digital output type	IO-Link, PNP
I/O connection type	M12
Number of I/O connectors	8
Height	240 mm
Width	62 mm
Depth	38 mm
Weight	440 g

Дополнительные принадлежности

1302011110	7/8 inch Waterproof Cover
72MDm4MDm4005K	Ethernet cable, PVC, M12 plug (D-coding, male) to M12 plug (D-coding, male), 0.5 m, green
72MDm4MDm4010K	Ethernet cable, PVC, M12 plug (D-coding, male) to M12 plug (D-coding, male), 1 m, green
72MDm4MDm4020K	Ethernet cable, PVC, M12 plug (D-coding, male) to M12 plug (D-coding, male), 2 m, green

	72MDm4MDm4030K	Ethernet cable, PVC, M12 plug (D-coding, male) to M12 plug (D-coding, male), 3 m, green
	72MDm4MDm4050K	Ethernet cable, PVC, M12 plug (D-coding, male) to M12 plug (D-coding, male), 5 m, green
	72MDm4MDm4100K	Ethernet cable, PVC, M12 plug (D-coding, male) to M12 plug (D-coding, male), 10 m, green
	72MDm4Rm4005K	Ethernet cable, PVC, M12 plug (D-coding, male) to RJ45, 0.5 m, green
	72MDm4Rm4010K	Ethernet cable, PVC, M12 plug (D-coding, male) to RJ45, 1 m, green
	72MDm4Rm4020K	Ethernet cable, PVC, M12 plug (D-coding, male) to RJ45, 2 m, green
	72MDm4Rm4030K	Ethernet cable, PVC, M12 plug (D-coding, male) to RJ45, 3 m, green
	72MDm4Rm4050K	Ethernet cable, PVC, M12 plug (D-coding, male) to RJ45, 5 m, green
	72MDm4Rm4100K	Ethernet cable, PVC, M12 plug (D-coding, male) to RJ45, 10 m, green
	72MNf4010	Power cable, PVC, 7/8 inch socket (female) to discrete wire, straight, 1 m
	72MNf4020	Power cable, PVC, 7/8 inch socket (female) to discrete wire, straight, 2 m
	72MNf4050	Power cable, PVC, 7/8 inch socket (female) to discrete wire, straight, 5 m
	72MNf4100	Power cable, PVC, 7/8 inch socket (female) to discrete wire, straight, 10 m
	72MNf4MNm4010	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), straight, 1 m

	72MNf4MNm4020	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), straight, 2 m
	72MNf4MNm4050	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), straight, 5 m
	72MNf4MNm4100	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), straight, 10 m
	72MNfL4010	Power cable, PVC, 7/8 inch socket (female) to discrete wire, right angle, 1 m
	72MNfL4020	Power cable, PVC, 7/8 inch socket (female) to discrete wire, right angle, 2 m
	72MNfL4050	Power cable, PVC, 7/8 inch socket (female) to discrete wire, right angle, 5 m
	72MNfL4100	Power cable, PVC, 7/8 inch socket (female) to discrete wire, right angle, 10 m
	72MNfL4MNmL4010	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), right angle, 1 m
	72MNfL4MNmL4020	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), right angle, 2 m
	72MNfL4MNmL4050	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), right angle, 5 m
	72MNfL4MNmL4100	Power cable, PVC, 7/8 inch socket (female) to 7/8 inch plug (male), right angle, 10 m
	XS2W-D421-D81-F	Cable with connectors on both cable ends, M12 straight socket (female), M12 straight plug (male), 4-poles, A coded, PVC fire-retardant robot cable, IP67, 2 m
	XS2W-D421-G81-F	Cable with connectors on both cable ends, M12 straight socket (female), M12 straight plug (male), 4-poles, A coded, PVC fire-retardant robot cable, IP67, 5 m
	XS2Z-22	Water-resistive Covers for M12-male connector



XS3W-M42C-4C2-A

Cable with connectors on both cable ends, M8 straight socket (female), Smartclick M12 straight plug (male), 4-poles, PVC standard cable, IP67, 0.2 m



XS5R-D426-1

Y-Joint plug/socket M12 SmartClick without cable (4-4, 4-2)

Загрузка

Библиотека дву-
/трехмерных CAD
рисунков



IO-Link Series
Брошюра

RU PDF 6,2 МБ




NXR Series IP67 Remote Terminal
Листовка

EN PDF 1,3 МБ



NXR-ILM08C-EIT
Спецификация

EN PDF 5,7 МБ



NXR-ILM08C-EIT
Файл EtherNet/IP EDS

EN ZIP 9,9 КБ



NXR-ILM08C-EIT IO-Link Master Unit for EtherNet/IP
Руководство пользователя

EN PDF 37,8 МБ



Sysmac
Каталог

RU PDF 44,2 МБ



Sysmac: A Fully Integrated Platform
Брошюра

EN PDF 10,4 МБ

УСЛОВИЯ ПОЛЬЗОВАНИЯ ВЕБ-САЙТОМ

Этот PDF-документ был создан на основании веб-сайта Европейского подразделения промышленной автоматизации компании OMRON 25 June, 2022. Нажмите здесь, чтобы ознакомиться с [уведомление о правах](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU