



PYF-08-PU

Колодка для реле MY, 8-pin (2 группы контактов), клеммы Push-in Plus

Технические характеристики

Applicable product family	MY2, MY2-GS
Mounting method	DIN rail/screw
Terminal	Push-in Plus
Width	31 mm
Height	90 mm
Depth	67.5 mm
Color	Black
Hold down clip included	✓
Release Lever included	✓

Также подходит



MY2 100/110VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 100/110 VDC



MY2 110/120VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 110/120 VAC



MY2 12VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 12 VAC



MY2 12VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 12 VDC

**MY2 220/240VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility

**MY2 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility

**MY2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility

**MY2 48/50VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 48/50 VAC

**MY2 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 48 VDC

**MY2-GS 24VDC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical indicator, 24 VDC

**MY2IN 110/120VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, test button, label facility

**MY2IN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility, 12 VAC

**MY2IN 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 220/240VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, test button, label facility

**MY2IN 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 48/50VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN-CR 220/240VAC (S)**

Relay, plug-in, DPDT, 10 A, mech. & LED indicator, test button, RC circuit, 220/240 VAC

**MY2IN-D2 12VDC (S)**

Relay, plug-in, DPDT, 10 A, mech. & LED indicator, test button, diode, 12 VDC



MY2IN-D2 24VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC



MY2IN-D2-GS 24VDC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, coil suppressor, lockable push test button, 24 VDC



MY2IN-GS 110/120VAC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 110/120 VAC



MY2IN-GS 220/240VAC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 220/240 VAC



MY2IN-GS 24VAC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 24 VAC



MY2IN-GS 24VDC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 24 VDC



MY2IN1 24VDC (S)

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, lockable push to test button, label facility



MY2IN1-D2 24VDC (S)

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC



MY2N 110/120VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 110/120 VAC



MY2N 12VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 12 VDC



MY2N 220/240VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 220/240 VAC



MY2N 24VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 24 VAC



MY2N 24VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 24 VDC



MY2N-CR 110/120VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility, 110/120 VAC



MY2N-CR 220/240VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility



MY2N-D2 12VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility, 12 VDC

**MY2N-D2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

**MY2N-D2-GS 24VDC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, coil suppressor, 24 VDC

**MY2N-GS 110/120VAC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 100/110 VAC

**MY2N-GS 220/240VAC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 220/240 VAC

**MY2N-GS 24VAC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 24 VAC

**MY2N-GS 24VDC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 24 VDC

**MY2N1-D2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

Дополнительные принадлежности

**MG-CPM-04 41390N**

White modular sheet with 48 marker of size mm: 5x10, Polycarbonate, Halogen Free, Silicon Free, UL94 V0, -40° to 130°C, Minimum Order Quantity is 1 box (In one box: 35 sheets, total markers 1680)

PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length

PFP-50N

Din rail track, 500 mm

**PFP-M**

End plate

**PYDN-15.5-080R**

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Red color

**PYDN-31.0-080S**

Accessory for PYF-PU, 31mm pitch, 8 Poles, Blue color

**PYDN-31.0-080Y**

Accessory for PYF-PU, 31mm pitch, 8 Poles, Yellow color

**PYDN-7.75-020R**


Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Red color

**PYDN-7.75-020S**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Blue color

**PYDN-7.75-020Y**


Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Yellow color

**PYDN-7.75-030R**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Red color

**PYDN-7.75-030S**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Blue color

**PYDN-7.75-030Y**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Yellow color

**PYDN-7.75-040R**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Red color

**PYDN-7.75-040S**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Blue color

**PYDN-7.75-040Y**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Yellow color

**PYDN-7.75-200R**

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Red color



PYDN-7.75-200S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Blue color



PYDN-7.75-200Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Yellow color



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

Загрузка

Библиотека дву-
/трехмерных CAD
рисунков



PYF-__-PU/P2RF-__-PU
Спецификация

EN PDF 3,1 МБ

УСЛОВИЯ ПОЛЬЗОВАНИЯ ВЕБ-САЙТОМ

Этот PDF-документ был создан на основании веб-сайта Европейского подразделения промышленной автоматизации компании OMRON 8 August, 2022. Нажмите здесь, чтобы ознакомиться с [уведомление о правах](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU