



PYF08S

Колодка для реле MY, 8-pin (2 группы контактов), пружинные клеммы

Технические характеристики

Applicable product family	G3F, H3YN, MY2, MY2 without CR, MY2-GS, MY2K
Mounting method	DIN rail/screw
Terminal	Screwless (Clamp method)
Width	23.2 mm
Height	85 mm
Depth	38.2 mm
Color	Beige
Hold down clip included	✘
Release Lever included	✘
Applicable wire	Solid, Stranded
Hold down clip for relay with CR circuit	Hold down clip cannot be used

Также подходит



MY2 100/110VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 100/110 VDC



MY2 110/120VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 110/120 VAC



MY2 12VAC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 12 VAC



MY2 12VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 12 VDC

**MY2 220/240VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility

**MY2 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility

**MY2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility

**MY2 48/50VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 48/50 VAC

**MY2 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 48 VDC

**MY2-GS 24VDC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical indicator, 24 VDC

**MY2IN 110/120VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, test button, label facility

**MY2IN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility, 12 VAC

**MY2IN 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 220/240VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, test button, label facility

**MY2IN 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 48/50VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN-CR 220/240VAC (S)**

Relay, plug-in, DPDT, 10 A, mech. & LED indicator, test button, RC circuit, 220/240 VAC

**MY2IN-D2 12VDC (S)**

Relay, plug-in, DPDT, 10 A, mech. & LED indicator, test button, diode, 12 VDC

**MY2IN-D2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC

**MY2IN-D2-GS 24VDC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, coil suppressor, lockable push test button, 24 VDC

**MY2IN-GS 110/120VAC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY2IN-GS 220/240VAC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY2IN-GS 24VAC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY2IN-GS 24VDC**

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY2IN1 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, lockable push to test button, label facility

**MY2IN1-D2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC

**MY2N 110/120VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 110/120 VAC

**MY2N 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 12 VDC

**MY2N 220/240VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 220/240 VAC

**MY2N 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 24 VAC

**MY2N 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, label facility, 24 VDC

**MY2N-CR 110/120VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility, 110/120 VAC

**MY2N-CR 220/240VAC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility

**MY2N-D2 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility, 12 VDC



MY2N-D2 24VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC



MY2N-D2-GS 24VDC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, coil suppressor, 24 VDC



MY2N-GS 110/120VAC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 100/110 VAC



MY2N-GS 220/240VAC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 220/240 VAC



MY2N-GS 24VAC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 24 VAC










MY2N-GS 24VDC

Relay, plug-in, 8-pin, DPDT, 7 A, mechanical & LED indicators, 24 VDC



MY2N1-D2 24VDC (S)

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

	PFP-S	Spacer
	PYCM-08S	Clip and release lever for PYF08S socket
	PYDM-08SR	Socket bridge, 2-poles, 19.7 mm length, red, sold in multiples of 50 per package
	R99-11	Nameplate for MY relay (packet of 100) (not PYF14ESN / ESS)
	XW5Z-EP12	Separator Plate for terminal blocks, 12 mm width
	Y92F-78	Flush panel mounting adapter for H3Y(N) timer
	Y92H-3	Clips for H3Y(N) timer & PYF socket

Библиотека дву-
/трехмерных CAD
рисунков



G3F/G3FD Solid State Relays

Спецификация

EN PDF 1,5 МБ



H3Y-series Solid-state Timers

Спецификация

EN PDF 8,9 МБ



H3YN Solid-state Timer

Спецификация

EN PDF 861,6 КБ



MY Miniature Power Relays - MY/MYQ/MYH

Спецификация

EN PDF 21,6 МБ



MY(S) Miniature Power Relays

Спецификация

EN PDF 11,5 МБ



MY-GS

Спецификация

EN PDF 4,6 МБ



PYC-0 Relay Sockets

Спецификация

EN PDF 207,2 КБ



PYC-35-B Relay Sockets

Спецификация

EN PDF 209,0 КБ



PYC-TR1 Relay Sockets

Спецификация

EN PDF 198,0 КБ



PYF-__-PU/P2RF-__-PU

Спецификация

EN PDF 3,1 МБ



PYF14-ESN-B Relay Sockets

Спецификация

EN PDF 619,8 КБ

УСЛОВИЯ ПОЛЬЗОВАНИЯ ВЕБ-САЙТОМ

Этот PDF-документ был создан на основании веб-сайта Европейского подразделения промышленной автоматизации компании OMRON 8 August, 2022. Нажмите здесь, чтобы ознакомиться с [уведомление о правах](#).