



## R88M-1M75030H-BS2

1S серво двигатель, 750 Вт, 230 VAC, 3000 об/мин, 2.39 Нм, инкрементальный энкодер, с тормозом

# Технические характеристики

Servo control method	EtherCAT
Drive supply voltage	230 V single phase
Rated output	0.75 kW
Rated speed	3000 Rpm
Rated torque	2.39 Nm
Peak torque	8.4 Nm
Encoder type	Incremental
Encoder resolution	23 Bit
Motor with brake	✓
Motor with oil seal	✗
Flange size square (LC)	80 mm
Shaft diameter	19 mm
Shaft with key	✓
Shaft with tap	✓
Weight	3500 g

## Также подходит



### **R88D-1SN08H-ECT**

1S servo drive, EtherCAT type, 800 W, 1~ 230 VAC

## Дополнительные принадлежности



**R88A-CA1A001-5BF-E**

1S series servo brake cable, 1.5 m, 230 V: 100 to 750 W



**R88A-CA1A001-5SF-E**

1S series servo motor power cable, 1.5 m, 230 V: 100 to 750 W



**R88A-CA1A003BF-E**

1S series servo brake cable, 3 m, 230 V: 100 to 750 W



**R88A-CA1A003SF-E**

1S series servo motor power cable, 3 m, 230 V: 100 to 750 W



**R88A-CA1A005BF-E**

1S series servo brake cable, 5 m, 230 V: 100 to 750 W



**R88A-CA1A005SF-E**

1S series servo motor power cable, 5 m, 230 V: 100 to 750 W



**R88A-CA1A010BF-E**

1S series servo brake cable, 10 m, 230 V: 100 to 750 W



**R88A-CA1A010SF-E**

1S series servo motor power cable, 10 m, 230 V: 100 to 750 W



**R88A-CA1A015BF-E**

1S series servo brake cable, 15 m, 230 V: 100 to 750 W



**R88A-CA1A015SF-E**

1S series servo motor power cable, 15 m, 230 V: 100 to 750 W



**R88A-CA1A020BF-E**

1S series servo brake cable, 20 m, 230 V: 100 to 750 W



**R88A-CA1A020SF-E**

1S series servo motor power cable, 20 m, 230 V: 100 to 750 W



**R88A-CR1A001-5CF-E**

1S series servo encoder cable, 1.5m, 230V: 50-750W



**R88A-CR1A003CF-E**

1S series servo encoder cable, 3m, 230V: 50-750W



**R88A-CR1A005CF-E**

1S series servo encoder cable, 5m, 230V: 50-750W



**R88A-CR1A010CF-E**

1S series servo encoder cable, 10m, 230V: 50-750W



**R88A-CR1A015CF-E**

1S series servo encoder cable, 15m, 230V: 50-750W



**R88A-CR1A020CF-E**

1S series servo encoder cable, 20m, 230V: 50-750W



**R88A-SC011S-E**

1S series cable clamp A. Used in 230 V drives up to 750 W

Библиотека дву-  
/трехмерных CAD  
рисунков



**1S Series**  
Руководство  
пользователя

EN PDF 26,6 МБ



**1S Series - Expanded  
with high capacity  
range: 4 - 15 kW**

Листовка

EN PDF 1,6 МБ



**1S Series Incremental  
Encoder Type Users  
Manual**

Руководство  
пользователя

EN PDF 41,2 МБ



**1S Series Multi-axis  
Setup and Tuning**  
Вводное руководство

EN PDF 3,5 МБ



**1S Servo System**  
Брошюра

RU PDF 5,9 МБ



**1S-series Servos**  
Справочник по  
командам

EN PDF 5,6 МБ



**AC Servomotor\_Servo  
Drives - Replace Guide**  
Руководство по замене

EN PDF 4,7 МБ



**Motor Sizing Tool**  
Руководство по  
эксплуатации

EN PDF 3,9 МБ



**Motor Sizing Tool  
V1.60.1.15**

Конфигуратор

EN ZIP 26,4 МБ



**R88M-1\_1S-series  
Servo Motor**  
Спецификация

EN PDF 1,6 МБ



**Redundancy and Motion  
Safety**  
Листовка

EN PDF 959,8 КБ



**Sysmac**  
Каталог

RU PDF 44,2 МБ



**Sysmac: A Fully  
Integrated Platform**  
Брошюра

EN PDF 10,4 МБ



**Using R88A-CA1G  
power cables**  
Технические сведения

EN PDF 1,6 МБ